



SOLID  
TO SUCCEED



MOBILE ELEVATING WORK PLATFORM

16<sup>m</sup> Li Series  
XG1614HD-li  
XG1614HA-li



The print does not belong to the contract, nor a part of the vehicle purchase contract. We reserve the right to revise the product model, parameters, configuration based on the continuous improvement requirements of the product, without prior notice. Pictures are for reference only, and the specific product shall depend on the real product.

**Parameter**

Item	Unit	XG1614HD-li	XG1614HA-li
<b>Dimension</b>			
Max. working height	m	15.8	15.8
Max. platform height	m	13.8	13.8
Overall length a	mm	2840	2840
Overall length (without ladder)	mm	2630	2630
Overall width b	mm	1390	1390
Overall height c	mm	2721	2721
Overall height (platform folded)	mm	2175	2175
Platform dimension (length d * Width e)	mm	2640 × 1120	2640 × 1120
Extended platform dimension	mm	900	900
Min. ground clearance (elevated/stowed state)	mm	20 / 77.5	20 / 77.5
Tire	mm	381 × 127	381 × 127
Wheelbase f	mm	2240	2240
<b>Performance</b>			
Max. number of occupants	/	2	2
Work platform rated load	kg	350	350
Extension platform rated load	kg	115	115
Travel speed (lowered/elevated position)	km/h	3 / 0.8	3 / 0.8
Min. turning radius (inside/outside wheel)	m	0 / 2.65	0 / 2.65
Work platform raising/lowering time	s	65-82 / 61-80	65-82 / 61-80
Max. gradeability	%	25	25
Tilt alarm angle (sideways/forward or back)	°	1.5 / 3	1.5 / 3
Total weight	kg	3680	3680
<b>Power source</b>			
Battery	/	Lithium battery	
Battery capacity	AH	228	
Options		AC power to the platform Air-line to platform Platform working light Weighing overload alarm	

